



**Examples  
Of  
Installation**


**Across Valve / Filter**



**Across Pump**



**Separately Powered**



**Technical Specifications :**

Min. Dosing Flow	- 1lph
Max. Dosing Flow	- 30 lph
Min. Actuation Pressure	- 0.3 bar
Max. Working Pressure	- 5.0 bar
Pressure loss at max. Flow	- 1.2 bar
Max. Operating Temperature	- 50°C
Inlet / Outlet Connections	- 3/4" BSPM
Dosing externally adjustable	- 0.5 to 2 %.

**Also available Fixed 2% Doser**



**Accessories Included**

1. Spares Kit
2. Wall/Tank Mounting Brackets
3. Suction Tubing with foot valve and filter
4. 3/4" Hose adaptors
5. 'O & M' Manual

PLEASE CONTACT :

**NUMATIK ENGINEERS PVT. LTD.**  
Shop No. 6, Bobby Pathak Avenue.  
Nr. Corporation Bank.  
Opp. Rotary Garden, C.S. Complex.  
Dahisar (East), Mumbai 400 068. India.  
Tel.: (022) 2848 2642 / 0866. 4014 2490  
Tele Fax : (022) 2848 0100

PLEASE CONTACT :

**NUMATIK ENGINEERS PVT. LTD.**  
Shop No. 6, Bobby Pathak Avenue.  
Nr. Corporation Bank.  
Opp. Rotary Garden, C.S. Complex,  
Dahisar (East) Mumbai 400 068. India.  
Tel.: (022) 2848 2642 / 0866. 4014 2490  
Tele Fax : (022) 2848 0100

Fax : 91-22-28480100